



PH-LED1940W



[View Details](#)

Introduction

This light can be placed horizontally, slanted or upside down to meet the needs of a variety of venues with 19x40W RGBW 4-in-1 LED. PH-LED1940W Suitable for theater, studio, conference, auditorium, multi-function hall and lecture hall.

Classification

Moving Head->Star Series

Product Description

ITEM: PH-LED1940W

Name: Wash moving head

Rated Voltage: AC100-240V

Frequency: 50 / 60Hz

Whole Lamp Rated Power: 650W

Beam Angle: 5-45° adjustable

Optical system

Light Source type: 19x40W RGBW 4-in-1 LED

Color temperature: 2500K~8000K adjustable

Scanner

X axis: 540°

Y axis: 240°

Automatic correction: Support

Control

Control method: DMX512, RDM, self-propelled, master-slave, voice control, built-in

Channels: 48CH/24CH

Other information

IP Rating: IP20

Signal Connection: 3 pins XLR input/output

Power Connection: Powercon input/output

Net Weight: 15kg

Measurement (LxWxH): 465×330×490 (mm)

Description:

- **This light can be placed horizontally, slanted or upside down to meet the needs of a variety of venues.**
- **LCD display, intuitive and easy to operate.**
- **0~100% linear dimming, soft and no flicker.**
- **The beam angle is adjustable, zoom angle 5-45°, switchable display of different effects.**
- **Strobe 1~25 times/second, adjustable speed, with instant dark field function.**
- **The middle effect can achieve infinite rotating dynamic effect, rich / dazzling color.**
- **With RGBW four-color infinite color mixing effect.**
- **Suitable for theater, studio, conference, auditorium, multi-function hall and lecture hall.**